

## Power Distribution

### Power Supplies—12 way PDU

Where many power adapters are required inside a 19" rack cabinet, the FP3301 can be used to supply mains voltage to up to 12 power adapters no higher than a combined power of 720W with a single mains lead input. The device is designed to fit into a standard 19" rack spacing occupying 74mm or max 2U in height. The depth is 195mm from the front mounting ears to the rear earth stud and allows two PDUs to be mounted back to back in a standard 600mm deep rack cabinet. Our range of 12V, 24V and 48V desktop power adapters fit the PDU.



#### DIMENSIONAL DRAWING

| Specifications               |   |
|------------------------------|---|
| <b>Standard</b>              | RoHS Compliant  |
| <b>Operating Temperature</b> | -15°C to 50°C   |
| <b>Weight</b>                | 3Kg Empty, Fully Loaded 6Kg                                       |
| <b>Height</b>                | 74mm 2U   |
| <b>Depth</b>                 | 195mm from front face. PSU leads may extrude 15mm from front face |
| <b>Current</b>               | Fully Loaded 4 Amps @230VAC                                       |
| <b>Voltage</b>               | 230-250VAC  |
| <b>Fuse</b>                  | 10A Slow Blow 5 x 20mm  |
| <b>Product code</b>          | UP-PDU12  |
| <b>Website location</b>      | SI-PD-PS-PDU12  |